

ZESTAWIENIE STALI KONSTRUKCYJNEJ

DLA RAM W OSIACH 2 I 13

Item Nr.	Term	Supply Kg	Supply unit
A	Member Truss H 43/120/112/120/43 x5 / , L= 1607, W= 400, T= 5.00	50	2
A	Member Truss H 43/120/112/120/43 x5 / , L= 4686, W= 400, T= 5.00	294	4
A	Member Truss H 43/120/112/120/43 x5 / , L= 5289, W= 400, T= 5.00	332	4
A	Joint Trussparts H 37/120/124/120/37 x5 / , L= 474, W= 400, T= 5.00	15	2
A	Conn. Truss-Column C 40/129/100/129/40 x5 / , L= 589, W= 400, T= 5.00	18	2
A	PLATE PL 200/300 x5 / , L= 300, W= 200, T= 5.00	38	16
A	Member Truss H 42/119/110/119/42 x4 / , L= 7427, W= 400, T= 4.00	373	4
A	Member Truss H 42/119/110/119/42 x4 / , L= 6808, W= 400, T= 4.00	342	4
A	Conn. Truss-Column C 40/125/100/125/40 x4 / , L= 414, W= 400, T= 4.00	21	4
A	Conn. Truss-Column C 40/125/100/125/40 x4 / , L= 419, W= 400, T= 4.00	21	4
A	STRUT IN FRAME C 17/75/100/75/17 x2 / , L= 1603, W= 268, T= 2.00	27	4
A	STRUT IN FRAME C 17/75/100/75/17 x2 / , L= 1671, W= 268, T= 2.00	28	4
A	STRUT IN FRAME C 17/75/100/75/17 x2 / , L= 1673, W= 268, T= 2.00	28	4
A	STRUT IN FRAME C 17/75/100/75/17 x2 / , L= 1740, W= 268, T= 2.00	29	4
A	STRUT IN FRAME C 17/75/100/75/17 x2 / , L= 1744, W= 268, T= 2.00	29	4
A	STRUT IN FRAME C 17/75/100/75/17 x2 / , L= 1812, W= 268, T= 2.00	30	4
A	STRUT IN FRAME C 17/75/100/75/17 x2 / , L= 1888, W= 268, T= 2.00	32	4
A	Column C 45/125/300/125/45 x5 / , L= 10042, W= 600, T= 5.00	1 892	8
A	Member Truss H 41/118/108/118/41 x3 / , L= 900, W= 400, T= 3.00	17	2
A	Conn. Truss-Column C 36/125/100/125/36 x3 / , L= 589, W= 400, T= 3.00	11	2
A	PILLAR-CONNECTION U 58/100/58 x4 / , L= 200, W= 200, T= 4.00	28	22

A Distance plate standard pillar PL 200/200x4 / , L= 200, W= 200, T= 4.00	28	22
A STRUT IN FRAME C 19/53/100/53/19 x3 / , L= 2112, W= 220, T= 3.00	44	4
A STRUT IN FRAME C 19/77/100/77/19 x3 / , L= 511, W= 268, T= 3.00	6	2
A STRUT IN FRAME C 19/77/100/77/19 x3 / , L= 663, W= 268, T= 3.00	8	2
A STRUT IN FRAME C 19/77/100/77/19 x3 / , L= 1571, W= 268, T= 3.00	40	4
A STRUT IN FRAME C 19/77/100/77/19 x3 / , L= 1654, W= 268, T= 3.00	42	4
A STRUT IN FRAME C 19/77/100/77/19 x3 / , L= 1612, W= 268, T= 3.00	41	4
A CONNECTION PROFILE FRAME-BRACE SEE SCHABLON DRAWING / , L= 400, W= 268, T= 3.00	10	4
A STRUT IN FRAME C 28/82/100/82/28 x4 / , L= 1486, W= 290, T= 4.00	54	4
A STRUT IN FRAME C 28/82/100/82/28 x4 / , L= 1439, W= 290, T= 4.00	52	4
A STRUT IN FRAME C 28/82/100/82/28 x4 / , L= 1448, W= 290, T= 4.00	53	4
A STRUT IN FRAME C 28/82/100/82/28 x4 / , L= 1526, W= 290, T= 4.00	56	4
A STRUT IN FRAME C 28/82/100/82/28 x4 / , L= 1129, W= 290, T= 4.00	41	4
A JOINT IN TRUSS U 59/104/59 x6 / , L= 200, W= 600, T= 6.00	92	20
A STRUT IN FRAME C 17/48/100/48/17 x2 / , L= 1807, W= 215, T= 2.00	24	4
A STRUT IN FRAME C 17/48/100/48/17 x2 / , L= 1873, W= 215, T= 2.00	25	4
A Screw Hex cap 8.8 FZV Llentab + Nut M12x37 (3-16) + M12 /	93	1 520
A Screw Hex cap 8.8 FZV Llentab + Nut M12x45 (15-25) + M12 /	1	16
A M10 clamp M10 / , L= 160, T= 10.00		8
A DISTANCE PLATE C-250D for M20 PL 290/272 x4 / , L= 272, W= 290, T= 4.00	20	8
A Pillar foot "250" 4xM20 for braces 250 M20 / , L= 240, W= 300	62	4
A Washer FZV 13x24x8 /	26	1 536
A Nut hex 8 FZV M10 /		16
A Washer FZV 10.5x22x2 /	0	16

Unit

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS

PCS