

ZESTAWIENIE STALI KONSTRUKCYJNEJ

Item Nr.	Term	Supply Kg
A	Member Truss H 43/120/112/120/43 x5 / , L= 1607, W= 400, T= 5.00	50
A	Conn. Truss-Column C 40/129/100/129/40 x5 / , L= 589, W= 400, T= 5.00	18
A	Door Frame C 34/96/170/96/34 x4 / , L= 5579, W= 400, T= 4.00	140
A	U-Profile Z 51/40/51x2 / , L= 600, W= 134, T= 2.00	13
A	Z-Profile Z 51/40/51x2 / , L= 2025, W= 134, T= 2.00	17
A	Z-Profile Z 51/40/51x2 / , L= 2130, W= 134, T= 2.00	18
A	Member Truss H 41/118/108/118/41 x3 / , L= 900, W= 400, T= 3.00	17
A	Conn. Truss-Column C 36/125/100/125/36 x3 / , L= 589, W= 400, T= 3.00	11
A	CONNECTION PROFILE L 104/104 x4 / , L= 100, W= 200, T= 4.00	6
A	PLATE PL 50/50 x4 / , L= 50, W= 50, T= 4.00	1
A	STRUT IN FRAME C 19/77/100/77/19 x3 / , L= 511, W= 268, T= 3.00	6
A	STRUT IN FRAME C 19/77/100/77/19 x3 / , L= 663, W= 268, T= 3.00	8
A	BRACE TYPE D PL 42/1079 x4 / , L= 1079, W= 42, T= 4.00	3
A	BRACE TYPE D PL 42/2155 x4 / , L= 2155, W= 42, T= 4.00	6
A	BRACE TYPE E DIVIDED IN 4 PARTS / , L= 3000, W= 200, T= 4.00	9
A	C-Profile C 28/82/100/82/28 x4 / , L= 720, W= 290, T= 4.00	40
A	Z-250 Z 20/60/250/60/20 x2 / , L= 7725, W= 400, T= 2.00	146
A	RIDGEPROFILE L 85/25 x2 / , L= 2500, W= 107, T= 2.00	8
A	CONSOLE VERTICAL U 60/100/60 x2 / , L= 448, W= 215, T= 2.00	9
A	CONSOLE HORIZONTAL U 60/100/60 x2 / , L= 1102, W= 215, T= 2.00	22

A	EAVES PROFILE U 95/73/58 x2 / , L= 2500, W= 215, T= 2.00	17
A	Washer FZV 13x24x8 /	5
A	Stretching screw M16 (for M12 screw) CE M16 /	2
A	Screw Hex cap 8.8 FZV Llentab + Nut M12x37 (3-16) + M12 /	18
A	Connection profile L 94/115 x5 / , L= 190, W= 245, T= 5.00	7
A	Conn.profile Reinf. Frame L 113/113 x3 / , L= 70, W= 220, T= 3.00	5
A	CONSOLE CANOPY 21° U 60/100/60 x2 / , L= 1160, W= 215, T= 2.00	23

Delivery Weight 627

**Supply
unit Unit**

2 PCS

2 PCS

2 PCS

10 PCS

4 PCS

4 PCS

2 PCS

2 PCS

10 PCS

10 PCS

2 PCS

2 PCS

2 PCS

2 PCS

2 PCS

6 PCS

3 PCS

2 PCS

6 PCS

6 PCS

2 PCS

300 PCS

2 PCS

300 PCS

4 PCS

12 PCS

6 PCS